



**Rough Wall Opening**  
12-5/8" (320mm) wide  
26-5/8" (675mm) high  
4" (102mm) minimum  
recessed depth

**MATERIALS:**

**Cabinet** — 18-8 S, type-304, 22-gauge (0.8mm) stainless steel. All-welded construction. Exposed surfaces have satin finish.

**Flange** — 18-8 S, type-304, 22-gauge (0.8mm) stainless steel with satin finish. Drawn and beveled, one-piece, seamless construction.

**Door** — 18-8 S, type-304, 22-gauge (0.8mm) stainless steel with satin finish. Secured to cabinet with a full-length stainless steel piano-hinge. Equipped with a tumbler lock keyed like other Bobrick washroom accessories.

**Receptacle Panel** — 18-8 S, type-304, 22-gauge (0.8mm) stainless steel with satin finish. Secured to door with a spring-loaded, full-length stainless steel piano-hinge. Equipped with an international graphic symbol identifying waste disposal.

**Waste Container** — Removable, leak-proof, rigid molded plastic. Capacity: 3 gal. (11.4 L).

**OPERATION:**

Unit is equipped with a self-closing panel covering receptacle opening. Waste receptacle is emptied by opening door with furnished key and removing waste container.

**INSTALLATION:**

Provide framed rough wall opening 12-5/8" wide x 26-5/8" high (320 x 675mm). Minimum recessed depth required from finish face of wall is 4" (102mm). Allow clearance for construction features that may protrude into rough wall opening from opposite wall. Coordinate with mechanical engineer to avoid pipes, vents, and conduits. If unit projects above top of wainscot, provide aluminum channel or other filler to eliminate gap between flange and finish face of wall. Mount unit in wall opening with shims between framing and cabinet at all points indicated by an S, then secure unit with #8 x 1/4" (4.2 x 32mm) sheet-metal screws (not furnished).

**SPECIFICATION:**

Recessed covered waste receptacle shall be type-304 stainless steel with all-welded construction; exposed surfaces shall have satin finish. Flange shall be drawn and beveled, one-piece, seamless construction. Door shall be secured to cabinet with a full-length stainless steel piano-hinge and equipped with a tumbler lock keyed like other Bobrick washroom accessories. Unit shall have a self-closing panel covering receptacle opening. Panel shall be secured to door with a spring-loaded, full-length stainless steel piano-hinge and equipped with an international graphic symbol identifying waste disposal. Unit shall be furnished with a removable, leak-proof, rigid molded plastic waste-container with a minimum capacity of 3 gal. (11.4 L). Manufacturer's service and parts manual shall be provided to the building owner/manager upon completion of project.

**Recessed Covered Waste Receptacle shall be Model B-525 of Bobrick Washroom Equipment, Inc., Clifton Park, New York; Jackson, Tennessee; Los Angeles, California; Bobrick Washroom Equipment of Canada Ltd., Scarborough, Ontario; Bobrick Washroom Equipment Pty. Ltd. Australia; and Bobrick Washroom Equipment Limited, United Kingdom.**